

High Performance Linear Hall Sensor

XL47E

Features

- Specifically designed for Throttle Grip
- Built in reverse polarity protection on all pins (see Table 2)
- Built in anti-runaway function (see Figure 7 for chip characteristics)
- Built in active temperature compensation (see Figure 8 for chip characteristics)
- Anti-Surge of Input Terminal: >45V
- Operation Current: 5.5mA@V_{DD}=5.0V
- Wide Operating Voltage Range: 2.7V~7.5V
- Zero-point (No magnetic field) output voltage: 2.50V@V_{DD}=5.0V
- Sensitivity: 2.32mV/Gs@V_{DD}=5.0V
- Linearity: ±1%
- Low Noise Output Without External Capacitor Filtering
- Temperature Grade 1: -40 °C to 125 °C Ambient Operating Temperature Range
- Device HBM ESD Classification Level Class3A
- TO92S-3 package

General Description

XL47E is a wide voltage, wide linear range, and wide temperature range linear Hall sensor optimized for Throttle grip applications. It has functions such as anti reverse connection of any pin, anti runaway, and active temperature compensation. Its output voltage varies proportionally with the induced magnetic field strength, and its linear output voltage range follows the changes in power supply voltage. The typical operating voltage of XL47E is 5.0V, and the zero point output voltage (without magnetic field) at V_{DD}=5.0V defaults to 2.5V. The operating temperature range supports -40 °C~125 °C. The XL47E integrates high precision current source, temperature compensation module, Hall array, amplifier, driver module and other circuit modules, which provides high linearity and strong immunity to electromagnetic interference over the full voltage range and full temperature range.

Applications

- Throttle Grip

Typical application schematic




Figure1.XL47E Typical application schematic

High Performance Linear Hall Sensor

XL47E

Pin Configurations




Figure2.Pin Configuration of XL47E

Table1.Pin Description

Pin Number	Pin Name	Description
1	VDD	Supply Voltage Input Pin, XL47E operates from 2.7V to 7.5V DC voltage.
2	GND	Ground pin.
3	OUT	Output Pin.

Ordering Information

Order Information	Marking ID	Package Type	Eco Plan	Packing Type Supplied As
XL47E	XL47E	TO92S-3	RoHS & HF	1000 Units Per Bag

High Performance Linear Hall Sensor

XL47E

Function Block




Figure3.Function Block Diagram of XL47E

Absolute Maximum Ratings (Note1)

Parameter	Symbol	Value	Unit
Input Pin Voltage	V_{DD}	-0.3 ~ 25	V
Output Pin Voltage	V_{OUT}	-0.3 ~ 25	V
Input-Output Pin Voltage	V_{DD-OUT}	-7.5~7.5	V
Anti-Surge of Input Terminal	V_{DD_Surge}	45	V
Thermal Resistance(TO92S-3) (Junction to Ambient, No Heatsink, Free Air)	R_{JA}	160	°C/W
Operating Temperature	T_A	-40 ~ 125	°C
Operating Junction Temperature	T_J	-40 ~ 150	°C
Storage Temperature	T_{STG}	-65 ~ 150	°C
Lead Temperature(Soldering,10sec)	T_{LEAD}	260	°C
ESD(HBM)	—	≥4500	V

Note1: Stresses greater than those listed under Maximum Ratings may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operation is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

High Performance Linear Hall Sensor

XL47E

XL47E Electrical Characteristics (Note2)

$T_A = 25^{\circ}\text{C}$, $V_{DD} = 5.0\text{V}$, system parameters test circuit figure1, unless otherwise specified.

Parameters	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Operation Voltage	V_{DD}	–	2.7	5.0	7.5	V
Operation Current	I_{DD}	–	4.5	5.5	6.5	mA
Output Load Resistance	R_L	$B = -1250\text{Gs}$	–	8	–	$k\Omega$
Output Voltage Range	$V_{OUT(H)}$	$B = +1250\text{Gs}$	4.2	4.25	4.3	V
	$V_{OUT(L)}$	$B = -1250\text{Gs}$	0.8	0.85	0.9	V
Static Output Voltage	$V_{OUT(Q)}$	$B = 0\text{Gs}$	2.375	2.50	2.625	V
Linearity	Lin	–	–1	–	1	%
Ground Wire Open Circuit	$V_{GND-OFF}$	–	–	0.001	–	V
Output Resistance	R_{OUT}	–	–	40	100	Ω
Output Settling Time	–	$B = 0\text{Gs}$	–	2	–	μs
Output Noise	–	Bandwidth= 10Hz to 10kHz	–	0.7	–	mV

Note2:

(1) Linearity is the degree to which the static characteristic curve between the input and output quantities deviates from a straight line.

(2) The output settling time is defined as the time interval for the output voltage to settle to 90% of its static output voltage level.

XL47E Magnetic Characteristics (Note3)

Parameters	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Sensitivity	Sens	$V_{DD} = 5.0\text{V}$	2.181	2.32	2.459	mV/Gs

Note3:

(1) The magnetic South Pole (S) is defined as the positive magnetic field. The sensitivity in the table corresponds to measurements taken with the magnetic field perpendicular to the chip's marking surface.

(2) XL47E is optimized for throttle grip. When $V_{DD} = 5.0\text{V}$, the sensitivity corresponding to output voltage is in the linear range of 0.9V~4.2V as shown in the table.

High Performance Linear Hall Sensor

XL47E

XL47E Output Characteristics

$T_A = 25^\circ\text{C}$, system parameters test circuit figure1, test methods figure4, unless otherwise specified.




Figure4. Test Schematic of XL47E





Figure5. Output Characteristic Curve of XL47E ($V_{DD} = 5.0\text{V}$)

Note4: At room temperature, when $V_{DD}=5.0\text{V}$, the linear range of chip unipolar is 0.9V~4.2V.


High Performance Linear Hall Sensor

XL47E

Input reverse polarity protection characteristic curve

Figure 6. Input Reverse Polarity Protection Characteristic Curve of XL47E ($V_{DD} = -7.5 \sim 45V$)

Runaway Prevention Function Characteristic Curve

Figure 7. Runaway Prevention Function Characteristic Curve of XL47E ($V_{DD} = 5.0V$)

Note5: After the GND pin of the chip is disconnected, the OUT pin will be at a low level.

Active Temperature Compensation Function Characteristic Curve




Figure 8. Sensitivity versus temperature curve of XL47E of XL47E ($V_{DD} = 5.0V$)




Figure 9. Static output voltage versus temperature curve of XL47E ($V_{DD} = 5.0V$)





Figure 10. Output High/Low Level Temperature Characteristic Curve of XL47E

High Performance Linear Hall Sensor

XL47E

Package Information

TO92S-3



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.42	1.62	0.056	0.064
A1	0.66	0.87	0.026	0.034
b	0.33	0.56	0.013	0.022
b1	0.40	0.51	0.016	0.020
c	0.33	0.51	0.013	0.020
D	3.90	4.10	0.154	0.161
D1	2.28	2.68	0.090	0.106
E	2.90	3.25	0.114	0.128
e	1.27 REF		0.050 REF	
e1	2.44	2.64	0.096	0.104
L	13.50	15.50	0.531	0.610
θ	45° REF		45° REF	

High Performance Linear Hall Sensor**XL47E**

Important Notice

XLSEMI reserve the right to make modifications, enhancements, improvements, corrections or other changes without notice at any time. XLSEMI does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. XLSEMI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using XLSEMI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards. XLSEMI warrants performance of its products to the specifications applicable at the time of sale, in accordance with the warranty in XLSEMI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent XLSEMI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

For the latest product information, go to www.xlsemi.com.